

Specifications

Coil Ratings

Single- and Double-pole Relays

Rated voltage		Rated current		Coil resistance	Coil inductance (reference value)		Must operate voltage	Must release voltage	Max. voltage	Power consum. (Approx)
		50 Hz	60 Hz		Arm. OFF	Arm. ON				
AC	6 V	214.1 mA	183 mA	12.2 W	0.04 H	0.08 H	80%ax.	30% min.	110 %	1.0 to 1.2 VA (60 Hz)
	12 V	106.5 mA	91 mA	46 W	0.17 H	0.33 H				
	24 V	53.8 mA	46 mA	180 W	0.69 H	1.30 H				
	50 V	25.7 mA	22 mA	788 W	3.22 H	5.66 H				
	100/110 V	11.7/12.9 mA	10/11 mA	3,750 W	14.54 H	24.6 H				
	110/120 V	9.9/10.8 mA	8.4/9.2 mA	4,430 W	19.20 H	32.1 H				
	200/220 V	6.2/6.8 mA	5.3/5.8 mA	12,950 W	54.75 H	94.07 H				
220/240 V	4.8/5.3 mA	4.2/4.6 mA	18,790 W	83.50 H	136.40 H					
DC	6 V	150 mA		40 W	0.16 H	0.33 H	10% min.	0.9 W		
	12 V	75 mA		160 W	0.73 H	1.37 H				
	24 V	36.9 mA		650 W	3.20 H	5.72 H				
	48 V	18.5 mA		2,600 W	10.60 H	21.00 H				
	100/110 V	9.1/10 mA		11,000 W	45.60 H	86.20 H				

- Note: See notes on the bottom of this table